

specificaties nala

Spezifikationen / Specifications / Caractéristiques

Samenstelling Verbindung / compound / composé	100%PES
Gewicht (gr/m²) Weight / Poids	± 660 gr/m²
Breedte Breite / Width / Largeur	± 138cm
Rollengte Rollenlänge / Roll length / Longueur du rouleau	± 30 m

TEST PRÜFEN	NORM NORME	RESULTAAT ERGEBNIS / RESULT/ RÉSULTAT
Martindale	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	> 100.000
Weerstand tegen pilling Resistenz gegen Pilling Resistance to pilling Résistance au boulochage	DIN EN ISO 12945-2:2000-11. 2000 cycles	4-5
Kleurvastheid bij licht Farbechtheit gegenüber Licht Color fastness to light Solidité des couleurs à la lumière	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5	5
Kleurvastheid bij wrijven Farbechtheit gegenüber Reiben Colour fastness to rubbing Solidité des couleurs au frottement	DIN EN ISO 105-X12:2016-11	4-5

Wasvoorschrift Waschanleitung / Washing instructions Instructions de lavage	
Toepassing	

Kenmerken Eigenschaften / Characteristics / Caractéristiques	
--	--

nala

Stalenkaart
Munsterkarte
Sample Card
Exemple de carte

koest






01



02



03



12



04




05



06




13



07




14



15

Makkelijk onderhoud
Einfache Wartung
Easy maintenance
Entretien facile



08



16




17



18




09




10



11



19



20

